

LTS Research Laboratories, Inc. Safety Data Sheet Aluminum Silicon

1. Product and Company Identification	
Trade Name:	Aluminum silicon alloy
Chemical Formula:	Al/Si
Recommended Use:	Scientific research and development
Manufacturer/Supplier:	LTS Research Laboratories, Inc.
Street:	37 Ramland Road
City:	Orangeburg
State:	New York
Zip Code:	10962
Country:	USA
Tel #:	855-587-2436 / 855-lts-chem
24-Hour Emergency Contact:	800-424-9300 (US & Canada)
	+1-703-527-3887 (International)
	2. Hazards Identification
Signal Word:	Danger
Hazard Statements:	H228 Flammable solid
	H228 Flammable solid H261 In contact with water releases flammable gas
Hazard Statements: Precautionary Statements:	H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No
	H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking
	H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder P402+P404 Store in a dry place. Store in a closed container
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder P402+P404 Store in a dry place. Store in a closed container P501: Dispose of contents/container in accordance with
	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder P402+P404 Store in a dry place. Store in a closed container
Precautionary Statements:	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder P402+P404 Store in a dry place. Store in a closed container P501: Dispose of contents/container in accordance with
Precautionary Statements:	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder P402+P404 Store in a dry place. Store in a closed container P501: Dispose of contents/container in accordance with local/regional/national/international regulations
Precautionary Statements: HMIS Health Ratings (0-4):	 H228 Flammable solid H261 In contact with water releases flammable gas P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking P231+P232 Handle under inert gas. Protect from moisture P280 Wear protective gloves/protective clothing/eye protection/face protection P240 Ground bond container and receiving equipment P241 Use explosion-proof electrical/ventilating/lighting/equipment P370+P378 In case of fire: Use CO₂, sand, extinguishing powder P402+P404 Store in a dry place. Store in a closed container P501: Dispose of contents/container in accordance with local/regional/national/international regulations Powder Bulk

	3. Composition
Chemical Family: Additional Names:	Metal alloy
Aluminum (Al):	
Percentage:	0-100 wt.%
CAS #:	7429-90-5
EC #:	231-072-3
Silicon (Si):	
Percentage:	0-100 wt.%
CAS #:	7440-21-3
EC #:	231-130-8
	4. First Aid Procedures
General Treatment:	Seek medical attention if symptoms persist.
Special Treatment:	None
Important Symptoms:	None
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult.
Ingestion:	Give one to two glasses of water and induce vomiting. Never induce
C	vomiting or give anything by mouth to an unconscious person.
Skin:	Wash affected area with mild soap and water.
Eyes:	Flush eyes with water, blinking often for several minutes.
	5. Firefighting Measures
Flammability:	Non-flammable, except as powder
Extinguishing Media:	Do not use water for metal fires – use CO ₂ , sand, extinguishing powder.
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.
	6. Accidental Release Measures
If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust. Keep away from ignition sources.
Environmental Precautions:	Isolate runoff to prevent environmental pollution.
	7. Handling and Storage
Handling Conditions:	Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store apart from
	materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with
Ventilation:	compressed air. Provide sufficient ventilation to maintain concentration at or below
	threshold limit.

8. Exposure Controls and Personal Protection		
Permissible Exposure Limits:	5 mg/m ³ as Si, long-term value	
Threshold Limit Value:	10 mg/m ³ as Si, long-term value	
Special Equipment:	None	
Respiratory Protection:	Use a respirator with type P100 (USA) or P3 (EN143) cartridges as a	
	backup to engineering controls. Risk assessment should be performed	
	to determine if air-purifying respirators are appropriate. Only use	
	equipment tested and approved under appropriate government	
	standards.	
Protective Gloves:	Rubber gloves	
Eye Protection:	Safety glasses or goggles	
	Full face protection	
Body Protection:	Protective work clothing. Wear close-toed shoes and long	
	sleeves/pants.	
9.	Physical and Chemical Characteristics	
Color	Silver grey	
Form:	Powder, Granules, Pellets, Sputtering target, Custom parts	
Odor:	Odorless	
Water Solubility:	Contact with water releases flammable gases as powder/ Insoluble as	
Bulk	NT/A	
Boiling Point:	N/A	
Melting Point: Flash Point:	577-1414 °C N/A	
Autoignition Temperature:	N/A N/A	
Density:	NA	
Molecular weight:	N/A C Research	
	10. Reactivity	
Stability:	Stable under recommended storage conditions	
Reacts with:	Strong oxidizing agents ,Water to release flammable gases which may	
	ignite instantly	
Incompatible Conditions/Materials:	Oxidizing agents, Water/Moisture, Bases	
Hazardous Decomposition Products:	Silicon oxide, Aluminum oxide, Metal oxide fumes	
	11. Toxicological Information	
Potential Health Effects:		
Eyes:	May cause irritation	
Skin:	May cause irritation	
Ingestion:	May cause irritation	
Inhalation:	May cause irritation	
Chronic:	N/A	
Signs & Symptoms:	N/A	
Aggravated Medical Conditions:	N/A	
Median Lethal Dose:	N/A	
Carcinogen:	Aluminum may be implicated in Alzheimer's disease. Inhalation of aluminum containing dusts may cause pulmonary disease. Inorganic silicon compounds/silicon metal may be acute inhalation irritants. Prolonged inhalation may cause pulmonary fibrosis known as silicosis.	

	12. Ecological Information
Aquatic Toxicity:	N/A
Persistent Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative: Notes:	No
	Do not allow undiluted product or large quantities to reach ground
	water, water course or sewage system. Avoid transfer into the environment
	13. Disposal Considerations
Dispose of in accordance with local, state	, national, and international regulations.
	14. Transportation Data
Hazardous:	Hazardous as powder only.
Hazard Class:	4.3 Substances which, in contact with water, emit flammable gases
Packing Group:	III
UN Number:	UN1398
Proper Shipping Name:	Aluminum Silicon powder, uncoated
	15. Regulatory Information
	konstorias, inc.
Sec 302 Extremely Hazardous:	No.
Sec 304 Reportable Quantities:	N/A

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised:

03/31/2017